

THE BEST & STRONG “ EPOXY SYSTEMS”

Granite Look or Solid Color Flooring

THE BEST & STRONG Epoxy Systems

Granite Look or Solid Color Flooring

Introduction:

The THE BEST & STRONG Epoxy Systems are 100% solids epoxy floor coatings that provide a high build, durable, & chemical resistant floor. Finishes consist of a multi-color Granite Look broadcast system or one of the 6 solid colors.

Primary Use:

THE BEST & STRONG Epoxy Systems are designed to create a seamless floor coating in warehouses, restaurants, commercial kitchens, garages, and most residential and commercial applications.

Limitations:

Not for use in areas where waterproofing is required.

Packaging:


All of the THE BEST & STRONG Epoxy products are available in 1-½ gallon kits or 15-gallon kits.

Shelf Life:

One year from the ship date. Do not allow products to freeze. Do not store products in extreme heat or direct sunlight.

Color:

The THE BEST & STRONG Epoxy systems are available in 6 standard solid colors and 5 standard Granite Look blends. Custom color matching is available.



Job Conditions :

The ambient air and surface temperature must be a minimum of 10°C (50°F) and a maximum of 43°C (110°F) and shall remain so for at least 24 hours. Do not install over wet

substrates. The CV.ANUGERAH applicator shall inspect the substrate for any deficiencies and notify the architect or general contractor in writing of the corrections that need to be made before application of the CV.ANUGERAH products.

Application

1. Prepare the surface by mechanically abrading (shot



blasting, Grinding, Sanding, etc.) All dust, dirt, and surface contaminants shall be removed from the surface.

2. Fill all cracks with the manufacturer's ecommended crack/joint filler.

3. Apply the THE BEST & STRONG Epoxy Primer at a rate of 300 sq. ft. per gallon. (*Primer coat optional for Granite Look Finish*)

4. Apply the THE BEST & STRONG Epoxy Pigmented at a rate of 150-200 sq. ft. per gallon.

(FOR GRANITE LOOK: Broadcast the premix acrylic color chips into the wet epoxy until refusal. After product has cured remove loose chips)

5. Apply the THE BEST & STRONG Epoxy Clear at a rate of 150-200 sq. ft.per gallon. If the floor is exposed to sunlight use the THE BEST & STRONG Urethane 200 or 100 as the topcoat to minimize discoloration.

Limitations:

- Read all of the complete CV.ANUGERAH application instructions.
- Top coats may be slippery
- Do not apply in temperatures below 50°F or temperatures above 95°F.

Maintenance:

Floors can be cleaned with water and a mild detergent. Detergents shall be completely removed from the floor after cleaning.

Warranty:

Pli-Dek, Inc. guarantees that the materials are free from defects. Contact CV.ANUGERAH for details.

Technical Assistance:

CV.ANUGERAH Systems, Inc. or its local authorized representatives are available for technical on-site assistance with the CV.ANUGERAH line of products.

Distributed : CV. ANUGERAH – WATERPROOF

Telp :031-7670735 Fax : 031- 7672945

www.anugerahwaterproof.com